

Declaration of Performance

N° DoP: 2024-001 SA55



Unique identification code of the product-type:	ONDUCLAIR® PLR GO110 177/51, ONDUCLAIR® PLR PO112 76/18, ONDUCLAIR® PLR Corrugated Roll, ONDUCLAIR® PLR Flat Roll,
Intended use/es:	Light transmitting single skin profiled GRP sheets for discontinuously roof covering for buildings and/or for internal and external wall and ceilings finishes.
Manufacturer:	Onduline 5-7 rue Frédéric Clavel 92150 Suresnes - France
System/s of AVCP:	System 4
Harmonised standard :	EN 1013:2012 + A1:2014
Notified body/ies:	-

Declared performances:

Essential characteristics	Performance	Tolerance		Harmonised standard
		minimum	maximum	
Reaction to fire (class)	E,s3,d0	-	-	EN 1013:2012 + A1:2014
External fire performance (class)	NPD	-	-	
Mechanical resistance	NPD	-	-	
Flexural Tensile strength	NPD	-	-	
Water vapour permeability (mg/m.h.Pa)	1,5.10 ⁻⁵	-	-	
Water/air tightness	Pass	-	-	
Dimensional tolerances	Pass	-	-	
Light transmittance (Cristal) (%)	84,3	-	-	
Durability, as variation of yellowness index	NPD	-	-	
Durability, as variation of light transmittance	NPD	-	-	
Durability, as variation of flexural/tensile strength	NPD	-	-	
Release of dangerous substances	No dangerous substances above the acceptable limits	-	-	
Resistance to fixings	Principles of fixing are available on the Onduline website	-	-	

NPD* : No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number : v02

Signed for and on behalf of the manufacturer by:
Nay TAWILE
Suresnes, 02/12/2024